

TT-2200 GPS Tracking Device

Ideal use-case for this device: Non-Powered Equipment and Other Assets



This battery-powered device is ideal for tracking non-powered equipment (e.g., cargo, water pumps, etc.) located in remote areas with little or no cellular coverage.

Key Features

- Global coverage
- Low maintenance
- Quick and easy install

Options

- Field-replaceable battery
- Flexible reporting frequency

TT-2200 Specifications

COMMUNICATIONS

Satellite Global LEO Satellite operation using the Globalstar Simplex Data Network

CERTIFICATIONS

FCC CFR Parts 15 and 25

Industry Canada

CE Mark

ANATEL (pending)

COFETEL (pending)

ENVIRONMENTAL

Temperature -30° to +60° C (Note, the device shall remain operational over the -40° to 85°C range, though battery life and RF signal degradation may occur.)

ELECTRICAL

Battery Type

Battery Technology (4) AAA 1.5 V Lithium

Battery Life 1.5+ years

PHYSICAL

Dimensions 2.7" x 3.25" x 1" (with brackets)
(68.58 x 82.55 x 25.4 mm)

Weight 3.6 oz (102 g) (with 4 batteries and mounting hardware)

MOUNTING

Industrial adhesives, brackets or screw mounts